

ADKCD653RP

1/3" Sony 650/700 TVL
2.8-10 mm, 12V, IR
21 LED, WDR, DNR, OSD,
indoor dome



Key Features

- Internal Dome features
- Small modern design
- 3Axis movement
- 21pcs IR LED
- 2nd Video RCA
- OSD joystick Control
- Wall and flush ceiling mount in one housing

Technical Specifications

	ADKCD653RP
Camera type	Indoor Dome
Casing color/material	White/Polycarbonate
Signal System	PAL
Image Sensor	1/3" Sony ExView HAD II CCD
DSP name	Effio-E Enhanced
Effective Pixels	976 (H) x 582 (V)
Horizontal Resolution	650 TVL (Color), 700 TVL (B/W)
IR LED	21pcs
IR LED Beam Distance	10m
Video output	1.0Vp-p Composite. 75 Ohms
S/N ratio	More than 52dB
Day & Night	By IR LED
Min. Illumination	0.1Lux/F1.2 (IR Off), 0Lux IR On
Digital Slow Shutter	N/A
Sense UP	N/A
Wide Dynamic Range	Digital
Privacy Masking	Yes
Digital Noise Reduction	Yes
Motion Detection	Yes
Digital Zoom	N/A
Sync System	INT
Shutter Speed	PAL: 1/50 ~ 1/100,000 sec
White Balance	ATW/Push/Anti-CR/Push lock
Lens	2.8-10 mm
OSD Control	Yes
Power Voltage	DC12V
Operating current	Max. 350mA
Power Consumption	Max. 4.5w
Weather Proof	N/A
Operating Temperature	(-10°C ~ +50°C) RH 95% Max
Weight net	500g
Weight gross	550g
Dimensions	130 (Dia) x 112 (H) mm
Box dimensions	172 x 162 x 182 (W x D x H) mm
Regulatory	CE/FCC/RoHS/WEEE

Dimensions

Unit: mm

