

GT999UNI

Vandal Proof IR Dome Camera

MAIN FEATURES

1/2.9" CMOS
2 Megapixel, 25fps @ 1080p
AHD/TVI/ CVI/ ANALOGUE 1080p
2.8-12mm Lens
25m Smart IR (30pcs IR LEDs)
Mechanic True Day & Night
AGC, AWB, BLC
Transmitting over 500m Coaxial cable
IP66
Built in cable management base



All-in-One
HD-TVI+ CVI AHD ANALOGUE



Built in
cable management base

Model	GT999UNI
Image Sensor	1/2.9" CMOS
Effective Pixels (H x V)	1936(H)×1096(V)
Resolution	2 Megapixel
Video Frame Rate	25fps @ 1080p
Electronic Shutter	Auto: 1/50-1/100, 000Sec
Synchronization	Internal
Min Illumination	Color 0.5Lux of F1.2 , 50IRE, AGC ON : (B/W) 0.001Lux of F1.2
Video Output	BNC AHD/TVI/CVI/ANALOGUE video output
Max. IR LEDs Length	25m Smart IR
IR LEDs	30pcs IR leds
Day/Night	Auto/External/color//BW
S/N ratio	>50dB
2D-DNR	0-100
3D-DNR	0-100
White balance	auto white balance
BLC/HLC	support
Private masking	support
Lens	2.8-12mm
Menu Language	Chinese/English
Transmission Distance	Over 500m via 75-3 coaxial cable
Power Supply	DC12V±10%
Ingress Protection	IP66
Power Consumption	Max 6.5W
Working Environment	-10°C~+60°C / Less than 95%RH
Dimensions(W×D×H)	150.05*120.73
Weight	840g