### IP Video Surveillance

VD7674W(WDR) WiFi Dome Camera

# 4MP Full HD 1080p



VIDEOTEKNIKA VD7674W is a compact, stylish and high impact vandal resistant fixed dome camera with WDR designed for indoor / outdoor applications with a 4 Megapixel sensor enabling a viewing resolution of 2688 x 1520 (Full HD 1080p Real Time). The multitasking day & night camera provides unleveled cost effective performance making the product a market leader in its segment. The camera allows versatile indoor use through its True Day & Night feature and its vandal resistance. The VD7674W camera incorporates a 1/3" CMOS chip with progressive scan technology enabling sharp images in highly populated locations. The VD7674W also supports POE.

#### Supported Compression

The VD7674W supports MJPEG compression technology, a digital video encoding standard where each video frame is separately compressed into a JPEG image. The VD7674W also supports the industry standard H.264+ compression, the most recent compres-sion technology that reduces drastically video file sizes therefore allowing for better storage and lowers bandwidth demands.

#### **Dual Streaming**

The VD7674W allows for dual independent streaming images to pass through the video coder. The resolution, frame rate and bit rate can be set independently on both streams. The main application for dual streams allows for high resolution and high frame rate streaming for recording while allowing lower resolution and frame rate for computer browsing and mobile device applications.

# VD7674W(WDR) IP 4MP WiFi Dome Full HD 1080p



















#### Supported Software

The Camera is supported by the Videoteknika VVMS-Xpert  $^{\text{\tiny TM}}$ VMS. The VVMS-Xpert  $^{\text{\tiny TM}}$ VMS is a modular Video Management Software dedicated for Videoteknika IP cameras expandable up to 1024 Channels per server. A 64 Ch version VVMS-Advanced is supplied as a free bundled software with all Videoteknika IP Cameras. VVMS-Mobile<sup>™</sup> is also available on Iphone and Android applications. Videoteknika IP cameras are supported by various leading software development VMS partners.

#### **Main Features**

- Full HD (1080p) Real time video
- Up to 4 Mega pixel (2688 x 1520) Resolution
- 1/3" progressive scan CMOS
- 2-Way Audio, Built-in Audio & Alarm Input/Output (Optional)
- IP67 & IK10 rated for Outdoor use
- Built-in IR Illuminator. Effective 30 metres
- 120DB Wide Dynamic Range
- True Day & Night IR Cut Filter (auto-switch)
- Fixed Lens 2.8 (Optional 4mm)
- **Dual Simultaneous Streaming**
- Supported Video Compressions: H.264/MJPEG/H.264+
- ROI, BLC, 3D-DNR, Privacy Masking, Reset, Mirror, etc.
- Protective Vandal Resistant IK10 rated Housing
- Power Over Ethernet (POE)
- WiFi (IEEE802.11b, 802.11g, 802.11n)
- NAS Network Storage Compatible
- ONVIF, PSIA, CGI compatible
- Built-in Micro SD / SDHC card slot for local storage
- Videoteknika VVMS-Advanced<sup>™</sup> VMS software included
- Videoteknika VVMS-Mobile<sup>™</sup> supported on App Store





# IP Video Surveillance

VD7674W(WDR) WiFi Dome Camera

# 4MP Full HD 1080p

#### Easy setup

- Power Over Ethernet POE (802.3af)
- WIFI (IEEE802.11b, 802.11g, 802.11n)
- · Polycarbonate dome with vandal resistance
- Saturation, brightness, contrast adjustable through client software or web browser
- Fixed Lens 2.8 (Optional 4mm)

XX VIDEOTEKNIK
----------------


Typical Camera Locations	VD7674W	
Retail	Yes	
Banking	Yes	
Airports	Yes	
Medical	Yes	
Parking garages	Yes	
Domestic	Yes	
Corporate	Yes	
Government	Yes	
Common Areas	Yes	


## **Specifications**

Camera Mode	era Model VD7674W		
Features			
Image Sensor		1/3" Progressive Scan CMOS	
Min. Illumination	on	O Lux with IR LED's On	
Shutter time		1/3s~1/10,000s	
Lens		2.8mm @ F1.4, Angle of view: 98°	
IR Range		30 metres	
Lens Mount		φ14	
Iris Mode		Fixed Iris	
Adjustment R	ange	Pan: 0°~355°, Tilt: 0°~75°	
Day and Night		IR cut filter with auto switch	
System Comp	atibility	ONVIF, PSIA, CGI	
Video Compre	ssion	H.264/MJPEG/H.264+	
Bit Rate		256 Kbps ~ 16 Mbps	
Dual Stream		Yes	
Max. Image Re	esolution	2688 x 1520	
Frame Rate	50 Hz: 2	O fps (2688 x 1520), 25 fps (1920 x 1080)	
	60 Hz: 2	O fps (2688 x 1520), 30 fps (1920 x 1080)	
Local Storage		Built-in SD/SDHC slot, up to 128 GB	
Ethernet Port		1x RJ45 10M / 100M Ethernet port	
Wide Dynamic Range		nic Range 120dB WDR	
Misc Configura	Misc Configurations 3D–DNR, BLC, ROI		

Camera Model	VD7674W			
Features (Continued)				
Alarm Input / Alarm Out	put 1 ch / 1 ch (Optional)			
Audio Input / Output	1-ch Mic in or Line in / 1-ch interface (Optional)			
Image Settings	Saturation, brightness, contrast adjustable			
	through client software or web browser			
Network Storage	NAS – Network Storage Compatible			
Alarm Trigger	Motion detection, network disconnect,			
IP address conflict, storage except				
Security	Password protection, watermark			
Wireless Standards	IEEE802.11b, 802.11g, 802.11n			
Wireless Security 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, W				
Environmental				
Operating Temperature	-30 °C ~ 60 °C (-22 °F ~ 140 °F)			
Electrical				
Input Voltage	12 VDC ± 10%, PoE (802.3af)			
Power Consumption Max. 5.5W				
Physical				
Dimensions 112 x 83 mm				
Protection IP67 & IK10				
Weight 510g (1.12lbs)				
Regulatory Certification	ons FCC, CE, C-TICK, UL			

### **Dimensional Diagrams**







# IP Video Surveillance VD7674W(WDR) Dome Camera



# 4MP Full HD 1080p

### **Ordering Information**

	Camera Details		
<b>VD7674W</b> 4MP (2688 x 1520), Full HD 1080p Real Time IP Dome, True Day & Night (ICR), Fixed 2.8 m			
	120dB WDR, WiFi, Dual Stream, 3-Axis, Vandal Proof, (VMS, Mobile & NAS Network Storage Support), SD Card		
	support.		

### **Recommended Associated Products**







VDB-03	VDB-04	VVMS-Advanced <sup>™</sup>
Pendant Mount Bracket	Wall Mount Bracket with Gang Box	Video Management Software
<2500 grams	<2500 grams	64 Channel
150 (W) x 545 (H) mm	140mm (L) x 193.6mm (W) x 297.5 (H) mm	Mobile Application

### **Affiliations:**





### **Partners:**

















